



- **autodrive stencil printer**
- **Technical data**
- **Frame size**
  - max. 584 x 584 mm
  - Rapid tensioning frame – 4 fold
  - another types of frames may be accepted
- **PCB size**
  - max. 440 x 440mm
- **Squeegee drive**
  - electric drive control
  - print speed 5-150mm/s
  - freely programmable squeegee travel
- **Squeegee changeover**
  - Automatic reversible dual squeegee
  - Universal holders for metal or rubber blade
  - adjustable squeegee inclination 0 - 60 °
  - adjustable squeegee contact pressure 0 - 200 N
- **Printing**
  - Single or double-sided boards
- **Table lowering**
  - automatic table lowering / Z=10 mm
  - lowering speed adjustable 0,2 - 4 mm/s
  - adjustable table contact pressure 0 - 450 N
- **Table - X, Y / Theta adjustment**
  - +/- 12 mm / +/- 2,7°
- **Off-Contact (Z-Axis) Range**
  - 0 -24 mm
- **Table - adjustment accuracy**
  - +/- 0,01 mm
- **Supply**
  - Compressed air 8 bar
- **Dimensions and wight**
  - 860 x 750 x 450 mm / ca. 90 kg
- **Application area**
  - low or middle volume production
  - screen- or stencilprinting of glue, solder paste or another substances
  - qualified for fine pitch components
  - minimum pitch of pads 0,3mm